

PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

FLED7PAR20940

7W PAR20 LED DIM 940

Fusion's FLED PAR20 lamps are designed to perform and provide accented and focused light. Fusion's advanced lens design is built to provide exceptional lumen output, extended life and an increase in energy savings.



FEATURES & BENEFITS:

- Long Life Equates to Lower Maintenance Costs
- Targeted and Controlled Light For Better Design
- Dimmable to 5% for design flexibility
- Contains no mercury or lead
- Damp location rated

APPROVALS





APPLICATIONS:

- Offices ambient lighting, task lighting, etc
- Retail Stores ambient lighting, showcase lighting, etc
- Restaurants Accent lighting, ambient lighting, atmosphere creations, etc.
- Hotels Accent lighting, ambient lighting, etc
- Recreational Facilities Accent lighting, ambient lighting,













ORDERING INFORMATION:

PART NUMBER	DESCRIPTION		CASE QTY	CASE DIMENSIONS	CASE WEIGHT	
FLED7PAR20940	7W PAR20 LED DIM 940	1	24	0.15"x10.59"x3.82"	6.62lbs	

OPERATING SPECIFICATIONS:

PART NUMBER	WATTS	EQUIVALENT WATTAGE	LUMENS	EFFICACY (LM/W)	ССТ	CRI	CERT1	DIMMABLE	RATED LIFE	WARRANTY
FLED7PAR20940	7	50	470	67	4000K	?90	cULus	Yes	25000	3



PPARTINUMBER:	DATE:
PRROLEIOT#:	TYPE:
PHREIPARKED BY:	

PART NUMBER:

FLED7PAR20940

7W PAR20 LED DIM 940

ELECTRICAL SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LAMP WATTS OPERATING VOLTAGE		POWER FACTOR	DRIVER	
FLED7PAR20940	7	120V	62	> 0.7	INTERNAL	

PHYSICAL SPECIFICATIONS:

PART NUMBER	LAMP STYLE	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	WEIGHT	OPERATING TEMP.	STORAGE TEMP.	LED TYPE	BEAM ANGLE
FLED7PAR20940	PAR20	E26	2.56	3.46	0.19	-20 [-4] to 45° [113]	-40 [-40] to 85 [185]	ACRICHE	40°













