



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

# FLED12PAR30SN930W

## 12W LED PAR30 SN 930 DIM

Fusion LED PAR30 SN lamps are designed to perform and offer incredible long life and high efficiency, making it a simple and cost effective switch.



**FEATURES & BENEFITS:**

- Long life equates to lower maintenance costs
- Dimmable
- Enclosed Rated
- Wet location rated

APPROVALS



**ORDERING INFORMATION:**

PART NUMBER	IMS CODE	DESCRIPTION	UNIT QTY	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED12PAR30SN930W	0448-7040	12W LED PAR30 SN 930 DIM	1	24	15.59x11.85x8.54	7.23

**OPERATING SPECIFICATIONS:**

PART NUMBER	WATTS	EQUIVALENT WATTAGE	LUMENS	EFFICACY (LM/W)	CCT	CRI	DIMMABLE	RATED LIFE	WARRANTY
FLED12PAR30SN930W	12	75	800	66.7	3000k	>90	Dimmable	15,000	3

\* System wattage/lumen performance subject to actual ballast factor ratings.



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

# FLED12PAR30SN930W

12W LED PAR30 SN 930 DIM

**ELECTRICAL SPECIFICATIONS:**

PART NUMBER	LAMP WATTS	LAMP OPERATING VOLTAGE	LAMP OPERATING CURRENT (mA)	OPERATING FREQUENCY	POWER FACTOR	DRIVER
FLED12PAR30SN930W	12	120	103	60Hz	>0.9	internal

\* Power Factor / Operating Voltage performance are ballast dependant

**PHYSICAL SPECIFICATIONS:**

PART NUMBER	LAMP STYLE	BULB FINISH	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	WEIGHT	OPERATING TEMP.	STORAGE TEMP.	BEAM ANGLE
FLED12PAR30SN930W	PAR 30 SN	N/A	E26	3.50	3.74	0.258	MINUS 20C-45C	MINUS 40-85C	40

