



43W LED T8 R17D D/E BYPASS

PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

FLED43T8R17D/840/DEBYPASS

43W LED T8 R17D 4K 8FT D/E BYPASS

Fusion T8 8ft linear tubes provide the efficiency of fluorescent technology in recessed, surface mounted and specialty fixtures. The 50,000hr lifetime of these lamps far outlast most fluorescent equivalents and provide savings on replacement labor and maintenance costs



FEATURES & BENEFITS:

- Double Ended wiring using existing tombstones
- Voltage range - 120-277V
- 50,000hr lifespan
- 5 year warranty

APPROVALS



ANSI CODE | C78.81



ORDERING INFORMATION:

PART NUMBER	IMS CODE	DESCRIPTION	UNIT QTY	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED43T8R17D/840/DEBYPASS	0429-4746	43W LED T8 R17D 4K 8FT D/E BYPASS	1	10	96.5"x7.5"x4.3"	13

OPERATING SPECIFICATIONS:

PART NUMBER	WATTS	EQUIVALENT WATTAGE	LUMENS	EFFICACY (LM/W)	CCT	CRI	DIMMABLE	RATED LIFE	WARRANTY
FLED43T8R17D/840/DEBYPASS	43	86	5500	127.9	4K	82	No	50000	5

* System wattage/lumen performance subject to actual ballast factor ratings.



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

FLED43T8R17D/840/DEBYPASS

43W LED T8 R17D 4K 8FT D/E BYPASS

ELECTRICAL SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LAMP OPERATING VOLTAGE	LAMP OPERATING CURRENT (mA)	OPERATING FREQUENCY	POWER FACTOR	SURGE PROTECTION	DRIVER
FLED43T8R17D/840/DEBYPASS	43	120-277	383	50/60	0.9	2.5KV	Internal

* Power Factor / Operating Voltage performance are ballast dependant

PHYSICAL SPECIFICATIONS:

PART NUMBER	LAMP STYLE	BULB FINISH	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	WEIGHT	OPERATING TEMP.	STORAGE TEMP.	LED TYPE	BEAM ANGLE
FLED43T8R17D/840/DEBYPASS	T8	IF	R17D	96	1	0.970	-20°F(-4°C) to 45°F(113°C)	-40°F(-40°C) to 85°F(185°C)	2835	185°

