

CATALOG #:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

# FL63/HID/WSCS/MOG

63W LED HID • WS(36W/54W/63W) • CS(3K/4K/5K) • MOG

Convert any HID fixture with the LED HID retrofit lamp series. The unique honeycomb design creates a 360° beam spread and helps dissipate heat maximizing longevity. The 50,000hr lifetime of these lamps far outlasts many HID equivalents saving you money on replacement labor and maintenance costs. Save in excess of 75% in energy costs of the equivalent wattage standard lamps.

FEATURES & BENEFITS:

- Replaces HID, CFL and Incandescent
- Ballast bypass - 120-277V AC
- Color selectable 3K/4K/5K
- Wattage selectable 36W/54W/63W
- Approved for enclosed fixtures.  
Min. enclosure size: (L)16.5" x (W)9.1" x (D)9.1"



ORDERING INFORMATION:

PART NUMBER	IMS CODE	DESCRIPTION	UNIT QTY	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FL63/HID/WSCS/MOG	0553-0743	63W LED HID WS(36W/54W/63W) CS(3K/4K/5K) MOG	1	12	15" x 11.4" x 12.7"	24.9 LBS

OPERATING SPECIFICATIONS:

LUMENS	36	54	63
3K	5040	7560	8820
4K	5580	8370	9765
5K	5400	8100	9450

EFFICACY	
3K	140
4K	155
5K	150

EQUIVALENT WATTAGE	
36	150W
54	200W
63	250W

CATALOG #:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

**ELECTRICAL SPECIFICATIONS:**

LAMP OPERATING VOLTAGE	OPERATING FREQUENCY	POWER FACTOR	CRI	RATED LIFE (HOURS)	WARRANTY
120-277V AC	50/60Hz	>0.9	>80	50,000 hrs	5-Years

**PHYSICAL SPECIFICATIONS:**

LAMP STYLE	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIAMETER. (MOD)	WEIGHT	OPERATING TEMP.	STORAGE TEMP.	LED TYPE	BEAM ANGLE
LED HID	E39	10.51" {267mm}	3.35" {85mm}	1.54LBS	-40° F - 113° F	-40° F - 176° F	2835	360°

**LINE DRAWING:**

