

| | |
|--------------|-------|
| CATALOG #: | DATE: |
| PROJECT #: | TYPE: |
| PREPARED BY: | |

PART NUMBER:

FL9A19840

9W LED A19 840 DIM

The FLED A19 Dimmable series from Fusion Lamps are designed to perform and offer incredibly long life, high efficacy, and easy integration within your existing lighting fixtures, making it a simple and cost effective switch.

FEATURES & BENEFITS:

- Dimmable
- Input 120V
- E26 base
- 3-year warranty
- Enclosed fixture rated
- Available in 2700K, 3000K, 4000K, and 5000K color temperatures.



KELVIN (CCT):

4000K 840

ORDERING INFORMATION:

| PART NUMBER | IMS CODE | DESCRIPTION | UNIT QTY | CASE QTY | CASE DIMENSIONS | CASE WEIGHT |
|-------------|-----------|--------------------|----------|----------|---------------------|-------------|
| FL9A19840 | 0582-4464 | 9W LED A19 840 DIM | 1 | 100 | 24.8" x 12.9" x 10" | 10.6 LBS |

OPERATING SPECIFICATIONS:

| PART NUMBER | LAMP WATTS | EQUIVALENT WATTAGE | INITIAL LUMENS | EFFICACY | CCT | CRI | CERT 1 | RATED LIFE (HOURS) | WARRANTY |
|-------------|------------|--------------------|----------------|-----------|-------|-----|--------|--------------------|----------|
| FL9A19840 | 9W | 60W | 800 lm | 89.0 lm/W | 4000K | >80 | cULus | 25,000 hrs | 3-Years |

| | |
|--------------|-------|
| CATALOG #: | DATE: |
| PROJECT #: | TYPE: |
| PREPARED BY: | |

ELECTRICAL SPECIFICATIONS:

| PART NUMBER | LAMP WATTS | LAMP OPERATING VOLTAGE | LAMP OPERATING CURRENT(MA) | OPERATING FREQUENCY | POWER FACTOR | SURGE PROTECTION RATING | RATED LIFE (HOURS) |
|-------------|------------|------------------------|----------------------------|---------------------|--------------|-------------------------|--------------------|
| FL9A19840 | 9W | 120V | 120 | 60Hz | >0.7 | 2.5KV | 15,000 hrs |

PHYSICAL SPECIFICATIONS:

| LAMP STYLE | BASE | MAX OVERALL LENGTH (MOL) | MAX OVERALL DIAMETER. (MOD) | WEIGHT | OPERATING TEMP. | STORAGE TEMP. | LED TYPE | NUMBER OF LEDS | BEAM ANGLE | ENCLOSED RATED |
|------------|------|--------------------------|-----------------------------|----------|-----------------|-----------------|----------|----------------|------------|----------------|
| A19 | E26 | 4.45" [113.03mm] | 2.40" [60.96mm] | 0.080LBS | -4° F - 104° F | -40° F - 104° F | SMD2835 | 16 | 220° | Yes |

LINE DRAWING:

