



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

FLED7.5R20840

7.5W LED R20 840 DIM

Fusion LED R20 lamps are designed to perform and offer incredible long life and high efficiency, making it a simple and cost effective switch.



FEATURES & BENEFITS:

- Long life equates to lower maintenance costs
- Dimmable to 5% for design flexibility
- Contains no mercury or lead
- Damp location rated

APPROVALS



ORDERING INFORMATION:

PART NUMBER	IMS CODE	DESCRIPTION	UNIT QTY	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED7.5R20840	0446-0655	7.5W LED R20 840 DIM	1	60	16.46x13.82x9.49	11.55

OPERATING SPECIFICATIONS:

PART NUMBER	WATTS	EQUIVALENT WATTAGE	LUMENS	EFFICACY (LM/W)	CCT	CRI	DIMMABLE	RATED LIFE	WARRANTY
FLED7.5R20840	7.5	50	525	70.0	4000k	80	Dimmable	15,000	3

* System wattage/lumen performance subject to actual ballast factor ratings.



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

FLED7.5R20840

7.5W LED R20 840 DIM

ELECTRICAL SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LAMP OPERATING VOLTAGE	LAMP OPERATING CURRENT (mA)	OPERATING FREQUENCY	POWER FACTOR	DRIVER
FLED7.5R20840	7.5	120v	80	60Hz	>0.7	INTERNAL

* Power Factor / Operating Voltage performance are ballast dependant

PHYSICAL SPECIFICATIONS:

PART NUMBER	LAMP STYLE	BULB FINISH	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	WEIGHT	OPERATING TEMP.	STORAGE TEMP.	BEAM ANGLE
FLED7.5R20840	Reflector	N/A	E26	3.74	2.48	0.112	MINUS 20C-45C	MINUS 40-85C	110

