



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

# FLED7.5R20850

## 7.5W LED R20 850 DIM

Fusion LED R20 lamps are designed to perform and offer incredible long life and high efficiency, making it a simple and cost effective switch.



**FEATURES & BENEFITS:**

- Long life equates to lower maintenance costs
- Dimmable to 5% for design flexibility
- Contains no mercury or lead
- Damp location rated

APPROVALS



**ORDERING INFORMATION:**

PART NUMBER	IMS CODE	DESCRIPTION	UNIT QTY	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED7.5R20850	0446-0658	7.5W LED R20 850 DIM	1	60	16.46x13.82x9.49	11.55

**OPERATING SPECIFICATIONS:**

PART NUMBER	WATTS	EQUIVALENT WATTAGE	LUMENS	EFFICACY (LM/W)	CCT	CRI	DIMMABLE	RATED LIFE	WARRANTY
FLED7.5R20850	7.5	50	525	70.0	5000k	80	Dimmable	15,000	3

\* System wattage/lumen performance subject to actual ballast factor ratings.



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

**FLED7.5R20850**

**7.5W LED R20 850 DIM**

ELECTRICAL SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LAMP OPERATING VOLTAGE	LAMP OPERATING CURRENT (mA)	OPERATING FREQUENCY	POWER FACTOR	DRIVER
FLED7.5R20850	7.5	120v	80	60Hz	>0.7	INTERNAL

\* Power Factor / Operating Voltage performance are ballast dependant

PHYSICAL SPECIFICATIONS:

PART NUMBER	LAMP STYLE	BULB FINISH	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	WEIGHT	OPERATING TEMP.	STORAGE TEMP.	BEAM ANGLE
FLED7.5R20850	Reflector	N/A	E26	3.74	2.48	0.112	MINUS 20C-45C	MINUS 40-85C	110

