

CATALOG #:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

# FLED15HID/5K/MEDV4

## 15W LED HID 5K MED

Fusion Lamps LED HID replacement lamps are designed to provide greater efficiency than HID technology in a number of different applications. The 50,000 hour lifetime of these lamps far outlast many HID equivalents saving you money on replacement labor and maintenance costs. Save in excess of 75% in energy costs of the equivalent wattage standard lamps.

FEATURES & BENEFITS:

- Replaces HID, CFL, and Incandescent
- Ballast bypass - 120-277V AC
- 5-year warranty
- 50,000 Hr lifetime
- Approved for enclosed fixtures  
Min. enclosure size: (L)12.2" x (W)7.5" x (D)7.5"

APPLICATIONS:

- For use in commercial, and outdoor settings such as acorns, post top, wall packs, shoe box and high bay fixtures



KELVIN (CCT):

**5000K** 850

ORDERING INFORMATION:

PART NUMBER	IMS CODE	DESCRIPTION	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED15HID/5K/MEDV4	0540-4206	15W FLED HID 5K MED	12	495 x 380 x 275mm - 19.5 x 15 x 10.8"	11.2kg - 24.7lbs

OPERATING SPECIFICATIONS:

PART NUMBER	LAMP WATTS	EQUIVALENT WATTAGE	INITIAL LUMENS	EFFICACY	CCT	CRI	Cert 1	Dimmable	RATED LIFE (HOURS)	WARRANTY
FLED15HID/5K/MEDV4	15W	60W	2100 lm	140.0 lm/W	5000K	>80	cULus	NO	50,000 hrs	5-Years

CATALOG #:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

**ELECTRICAL SPECIFICATIONS:**

PART NUMBER	LAMP OPERATING VOLTAGE	OPERATING FREQUENCY	DRIVER	POWER FACTOR
FLED15HID/5K/MEDV4	120-277V AC	50/60Hz	Internal	> 0.9

**PHYSICAL SPECIFICATIONS:**

PART NUMBER	LAMP STYLE	BULB FINISH	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	WEIGHT	OPERATING TEMP.	STORAGE TEMP.	LED TYPE	BEAM ANGLE	# OF LEDS
FLED15HID/5K/MEDV4	LED HID	CL	E26	5.71"	2.56"	0.62lbs	-40°F to 113°F	-40°F to 176°F	2835	360°	48

**LINE DRAWING:**

